

# CBMV-LED

## Construction:

- Steel chassis and decorative band
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Universal Mounting Pattern and hardware included
- Vertical or Horizontal mounting
- Open sides with LED light source
- ADA compliant
- **Build America, Buy America Act Compliant**
- UL and CUL listed **DAMP** location
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### CBMV-16

Height - 5"  
Depth - 2.5"  
Length - 16"



## ORDERING INFORMATION

Example: CBMV-16-LED-O2P-4-B1-WSA-DIM

### CBMV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O2P	12	1620	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black W1 Yolk White W2 Gloss White W3 Text White Z1 Satin Bronze Z3 Text Bronze T4 Shimmer Gray T6 Pewter M13 Anod Silver W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
								Optional (Consult Factory) M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286  
www.lightwayind.com • sales@lightwayind.com

