NOVA FLEX

Flexible Grazer Test Report

Light efficiency:

71 Lumen/Watt

Light quality:

CRI: 85.7

Color temperature:


4085 K

Output: 573 lm
Peak: 1235 cd


Power: 8.1 W
PF: 1.0

Tracking number: VT250711-004641

Product name:
GZF-BK-12-24-IP67-40
Item number:
GZF-BK-12-24-IP67-40
Date and time:
7/11/25 12:00:47 PM
All values scaled to 1 foot
From 0.75 M sample tested @ 11 M




Average Beam Angle




C Plane Resolution: 18°

Angular Distribution 0 ° Plane





Angular Distribution 90 ° Plane




NOVA FLEX

Color details






TM-30: 85.6



CRI: (R1-R8): 85.7



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
85.4	89.4	92.6	87.0	85.4	85.9	88.1	71.9	25.0	75.0	87.5	68.2	86.2	95.7	79.5


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
84.3	86.0	78.4	85.7	88.3	90.9	92.8	91.6	91.1	82.7	79.9	83.2	87.9	88.2	81.8	81.4

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
84.3	97.9	79.4	80.0	85.6	86.5	87.0	91.0	96.9	87.6	86.0	85.6	86.0	76.4	79.2

CQS: 84.8



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4085 K	85.7	25.0	85.6	99.1	84.8	0.376	0.372	0.224	0.333	-0.0010

NOVA FLEX

TM-30 details


Rf 85.6


Fidelity index Rf


Rg 99.1


Gamut index Rg


Hue Bin	R_f	Shifts (%) Chroma	Hue
1	84	-9%	-2%
2	86	-6%	5%
3	78	-3%	11%
4	86	2%	9%
5	88	5%	6%
6	91	6%	-1%
7	93	1%	-5%
8	92	-3%	-4%
9	91	-6%	1%
10	83	-7%	7%
11	80	1%	13%
12	83	5%	8%
13	88	9%	-4%
14	88	6%	-4%
15	82	2%	-14%
16	81	-3%	-12%















NOVA FLEX

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1235lx	309lx	137lx	77lx	49lx	34lx	25lx	19lx	15lx	12lx	10lx	9lx	7lx	6lx	5lx	5lx	4lx	4lx	3lx	3lx
114.8fc	28.7fcd	12.8fcd	7.2fcd	4.6fcd	3.2fcd	2.3fcd	1.8fcd	1.4fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1235	1210	1141	1040	923	805	693	594	508	433	370	317	272	234	203	176	153	135	118	104
100%	98%	92%	84%	75%	65%	56%	48%	41%	35%	30%	26%	22%	19%	16%	14%	12%	11%	10%	8%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1235	1210	1141	1040	923	805	693	594	508	433	370	317	272	234	203	176	153	135	118	104
100%	98%	92%	84%	75%	65%	56%	48%	41%	35%	30%	26%	22%	19%	16%	14%	12%	11%	10%	8%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1235	1210	1141	1040	923	805	693	594	508	433	370	317	272	234	203	176	153	135	118	104
100%	98%	92%	84%	75%	65%	56%	48%	41%	35%	30%	26%	22%	19%	16%	14%	12%	11%	10%	8%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1235	1210	1141	1040	923	805	693	594	508	433	370	317	272	234	203	176	153	135	118	104
100%	98%	92%	84%	75%	65%	56%	48%	41%	35%	30%	26%	22%	19%	16%	14%	12%	11%	10%	8%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
27°	70.5°	116.6°	92.7%	82.6%

Iso Diagrams

iso-candela diagram




10%	124 cd
20%	247 cd
30%	371 cd
40%	494 cd
50%	618 cd
60%	741 cd
70%	865 cd
80%	988 cd
90%	1112 cd

Conditions:

Number of c-planes: 20

Candela at center: 1235 cd

iso-lux diagram



Mounting height: 10 meters (33 feet)

3%	0.371 lx
5%	0.618 lx
10%	1.24 lx
30%	3.71 lx
50%	6.18 lx

Conditions:

Number of c-planes: 20

Lux at center: 12.4 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

NOVA FLEX

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18.2	19.0	18.4	19.2	19.4	18.9	19.6	19.0	19.9	20.1
	3H	18.7	19.6	19.1	19.8	20.0	19.5	20.4	19.9	20.6	20.8
	4H	19.0	19.8	19.4	20.1	20.3	20.0	20.8	20.4	21.0	21.3
	6H	19.3	20.0	19.6	20.3	20.7	20.5	21.2	20.8	21.4	21.8
	8H	19.4	20.1	19.7	20.4	20.8	20.6	21.3	21.0	21.6	22.0
	12H	19.4	20.1	19.8	20.4	20.9	20.8	21.4	21.1	21.8	22.2
4H	2H	18.4	19.2	18.8	19.5	19.7	19.0	19.8	19.4	20.0	20.3
	3H	19.3	19.9	19.6	20.3	20.7	20.0	20.7	20.4	21.0	21.4
	4H	19.6	20.2	20.0	20.6	21.1	20.5	21.1	20.9	21.5	22.0
	6H	19.9	20.6	20.4	20.9	21.3	21.0	21.6	21.5	22.0	22.3
	8H	20.1	20.6	20.6	21.0	21.4	21.3	21.8	21.8	22.2	22.6
	12H	20.1	20.6	20.6	21.0	21.5	21.5	21.9	22.0	22.3	22.8
8H	4H	19.8	20.3	20.3	20.7	21.1	20.6	21.1	21.1	21.5	21.9
	6H	20.2	20.7	20.7	21.1	21.6	21.3	21.7	21.8	22.1	22.7
	8H	20.5	20.8	21.0	21.3	22.0	21.6	22.0	22.1	22.5	23.1
	12H	20.6	20.9	21.2	21.4	22.0	21.9	22.2	22.5	22.7	23.3
12H	4H	19.7	20.2	20.2	20.6	21.1	20.5	21.0	21.0	21.4	21.9
	6H	20.3	20.7	20.8	21.2	21.8	21.3	21.6	21.8	22.2	22.8
	8H	20.5	20.8	21.1	21.3	21.9	21.7	21.9	22.2	22.4	23.0
Variation of the observer position for the luminaire distance S											
S = 1.0H		0.5 / -0.5					0.4 / -0.4				
S = 1.5H		1.3 / -1.0					1.1 / -0.7				
S = 2.0H		2.3 / -1.4					1.9 / -1.2				
CIE 117-1995. Corrected glare indices referring to 573 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	103	110	107	104	102	103	100	98	99	97	95	95	94	93	91
2	106	100	96	92	103	98	94	91	95	92	88	92	89	86	89	87	85	83
3	100	93	87	83	98	91	86	82	88	84	80	86	82	79	83	80	78	76
4	94	86	80	75	93	85	79	75	83	78	74	81	76	73	79	75	72	70
5	90	81	74	69	88	80	74	69	78	72	68	76	71	68	74	70	67	66
6	85	76	69	65	84	75	69	64	73	68	64	72	67	63	70	66	63	61
7	81	71	65	60	80	71	65	60	69	64	60	68	63	60	67	62	59	58
8	77	67	61	57	76	67	61	57	66	60	56	65	60	56	63	59	56	54
9	74	64	58	54	73	63	58	54	62	57	53	61	57	53	61	56	53	52
10	71	61	55	51	70	60	55	51	60	54	51	59	54	51	58	54	50	49

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
94.7 lm	153 lm	117 lm	79.7 lm	53.1 lm	34.1 lm	21.2 lm	12.8 lm	5.19 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.548 lm	0.470 lm	0.441 lm	0.398 lm	0.344 lm	0.279 lm	0.206 lm	0.126 lm	0.042 lm

LCS table

BUG rating:	B1 U0 G0	
Forward light	Lumens	Lumens %
Low(0-30):	183.2	31.9%
Medium(30-60):	83.9	14.6%
High(60-80):	17.1	3%
Very high(80-90):	2.6	0.5%
Back light		
Low(0-30):	183.2	31.9%
Medium(30-60):	83.9	14.6%
High(60-80):	17.1	3%
Very high(80-90):	2.6	0.5%
Uplight		
Low(90-100):	0	0%
High(100-180):	0	0%

