

RAZOR MK3

Ultra-Thin Die-Cast LED Exit Sign

The Razor MK3 Classic's 5/8" profile provides a modern, inconspicuous LED exit sign with wall, canopy, or pendant mounting options. Sophisticated electronics provide impressive energy efficiency, consuming just 2 watts. The illumination of 18fL is 7 times the minimum code requirements with a unique refractive-pattern light guide that distributes the LED evenly for flawless legend uniformity. Field-selectable top or end canopy mounting, snap-lock assembly, and optional square pendant rod with matching slim profile adapters and canopy simplify installation and improve versatility.



CONSTRUCTION

- Razor thin 5/8" Pressure Die Cast Aluminum. Available in Fine Grain Brushed Aluminum or powder coated pure White or Black finishes. Other finishes available to order
- Light Guide, light engine, batteries and electrical connectors are neatly housed in a single injection-molded frame assembly with flexible circuit board and simple mating connector.
- Mounts to standard 4S Junction box in Wall, Canopy or Pendant mount configurations
- Unique snap fit housing design eliminates unsightly hardware
- Removable face with field selectable Chevron directional indicators
- Low profile canopy for universal end or top mount applications
- Hang Straight 1/2" Extruded Aluminum matching Tube Pendant and adapters.
- Optional polycarbonate face shield with snap-fit installation ideal for vandal resistant and low level applications (U.L. listed for floor proximity installation)
- Also available with an additional remote powered sign (see data sheet RZMR3) or open face custom graphic (see data sheet RCG3)

ELECTRICAL

- Unique High intensity LED array provides exceptional energy efficiency with just 2 watts power consumption for both single and double face AC models. Battery backup models consume just 2.4 watts.
- Solid State circuitry provides optimum condition power supply for the LED's which are powered at less than 50% of their rated operating current ensuring minimal heat dissipation and subsequent exceptional LED life predicated to maintain 80% luminosity after 20 years continuous operation.
- Self-Diagnostic Battery monitoring on all 'EM' models
- Self-compensating constant current charger circuit monitors the condition of the battery pack and indicates via a flashing LED when battery needs replacing

- 120 or 277 VAC field selectable input
- Circuitry includes - Zero current LVCO, Brownout Sensing and Line-Latch
- Optional functions available: Self-Test, Self-Diagnostics, Fire Alarm Interface, Flash in Emergency Mode or Continuous Flash in AC mode, Infrared Remote testing (up to 40 feet away), Dual AC input and 2 Watt Remote Lamp Head Capacity.
- Premium High Temperature Maintenance free, eco-friendly Nickel Metal Hydride battery with fuse protection.
- Standard Battery Backup models are U.L. listed with 240 minutes emergency run time, 2.6 times longer than the 90 minute code requirement and assures optimum battery capacity over many years of natural depreciation. Remote lamp head rated models are U.L. listed for 90 minutes emergency run time.
- UL and CSA listed as standard "Suitable for use in damp locations 10° to 40° C"

ILLUMINATION

- Unique injection molded 3mm refractive light guide produces flawless uniformity and vibrantly illuminated 18fL legend - 7 times the minimum UL 924 requirement at a 100' viewing distance
- Red or Green LED with 6" letters and 3/4" stroke
- Maintenance free LED light source with 25+ year's life expectancy

CERTIFICATION

- Tested and Listed by Underwriters Laboratories in compliance with UL924 and CSA-C22.2 No. 14115. Razor also meets or exceeds all performance standards as required by NFPA 101 Life Safety Code, NFPA 70-NEC and OSHA
- California Energy Commission (CEC) Title 20 Compliant
- Buy American Act compliant

WARRANTY

- 5 year limited warranty - view complete warranty terms online at www.evenlite.com/terms-warranty.

ORDERING GUIDE

RZR3-EM-R-1-WH-CN-SD

MODEL	OPERATION	LETTER COLOR	NO. OF FACES	FACE & BODY COLOR	MOUNTING
RZR3	AC AC Only (120/277 VAC)	R Red	1 Single	BA All Brushed Aluminum	SURFACE MOUNT
	EM Battery Backup	G Green	2 Double	BK All Black	1B Wall Mount, No Canopy
			U Universal¹	WH All White	CN Canopy Universal, Top, Left, Right End
				CC Custom Color²	PENDANT MOUNT
					PA 12" Hang Straight Pendant Mount
					PB 24" Hang Straight Pendant Mount
					PC 36" Hang Straight Pendant Mount
					PD 48" Hang Straight Pendant Mount
					PE 60" Hang Straight Pendant Mount
					PF 72" Hang Straight Pendant Mount
RZR3					
OPTIONS					ORDERING NOTES 1 Universal includes two faces, backplate and canopy 2 Specify Color by RAL # or Manufacture detail 3 EM models only 4 Flash in Emergency Mode (EM Models) or Continuous Flash (AC models) 5 On 12-24V (AC or DC). Normally-off Fire Alarm signal (AC or EM models) 6 Field Selectable 120 or 277 VAC (AC models only) 7 Vandal-resistant snap lock clear polycarbonate cover. Available for Single or Double face signs in all mounting configurations. Listed for floor proximity installation 8 Order separately 9 Remote Lamp Head Options. Order Separately (Not to exceed 2 watts per master sign) 10 Wall mount only
OPTIONS		COMPATIBLE REMOTE HEADS³			
SD Self-Test/Self-Diagnostic³		M990010	Wire Guard¹⁰		
IR Self-Diagnostics with Infrared Remote Testing³		TCRH1	1 Watt Single Indoor LED Head		
F Flash in Emergency Mode⁴		TCRH2	1 Watt Each Double Indoor LED Head		
FA Flash in AC and Emergency mode⁵		PRWLED1MV	1 Watt Single Outdoor LED Head		
DK Two Circuit Input⁶		PRWLED2MV	1 Watt Each Double Outdoor Remote Head		
RC Remote Lamp Head Capacity (2 Watt, 3.6 Volts)					
RS Razor Polycarbonate Security Cover⁷					
TLRT Infrared Transmitter⁸					

Fill in fields from categories above and complete type and part number.

Type No:

Full Part No:

ADDITIONAL IMAGES




WHITE HOUSING
FINISH



BLACK HOUSING
FINISH



POLYCARBONATE
SECURITY COVER



CONSTRUCTION VIEW



OPTIONAL PRWLED1MV
Outdoor LED Remote
Lamp Head





OPTIONAL TCRH1
Indoor LED Remote
Lamp Head



BRUSHED
ALUMINUM FINISH
With Hang Straight Pendant

DIMENSIONS & MOUNTING

SURFACE MOUNT



UNIVERSAL MOUNT

