

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	45mm(1.77")
Length:	47mm(1.85")
Height / Projection:	73cm(2.87")

ELECTRICAL:

GH1115.AHFT400EC 1115.ALF.T




Number of heads:	1
Description:	1 x 6 W LED 3000 K CRI>90 1 x 845 lm
Luminaire efficiency:	97.36 lm/W
Fixture consumption:	7.06 W
Operation Range:	350 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	350 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	55°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Reflector in anti-UV technopolymer with super pure aluminum metallization




LIGHTING SOURCE:

Light source:	LED
Type of bulb or LED	COB
Light source:	6 W
Nominal LED emission:	845 lm
Color temperature:	3000K
Binning:	Step MacAdam 3
LED voltage range:	18V
Current:	350 mA
Color rendering index:	CRI90
Life Time LED:	60.000h - L80 - B10 [t]
Luminaire emission:	1 x 687lm
LED / Bulb	Included



H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	5.2	19	35
4	4.1	30	55
3	3.1	53	98
2	2.1	118	220
1	1.0	473	880





H(m)	φ (m)	lux med. 3000 K	lux max. 3000 K
5	5.2	19	35
4	4.1	30	55
3	3.1	53	98
2	2.1	118	220
1	1.0	473	880

FINISH OPTIONS:

Standard Finishes

●.05 Anthracite grey (matt)

●.19 Light grey (matt)

Upon Request Finishes

●.01 White (matt)

●.45 Corten (matt)

●.62 Antique grey (matt)

●.80 Sand (matt)

●.02 Black (matt)

●.26 Luxury bronze

●.65 Blue (matt)

●.83 Green (matt)

ACCESSORIES:



Stake 170mm
AC203



Hood Segno - Point Spot 2
AC647



IP 68 fast connector 4P
AC204

DIMMING TYPE:

101. Non-dimmable

102. 0-10V dimmable



sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake
Dr Richland, MI
49083 USA

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Series of spot lights to be mounted on floor, wall, spike, tree with belt system or on a pole system.
Gaskets:	Silicone gaskets
Construction material:	Stainless steel AISI 316L, Extruded aluminum EN AW-6063 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	45mm(1.77")
Length:	47mm(1.85")
Height / Projection:	73cm(2.87")

ELECTRICAL:

GH1115.BGST400EC 1115.BHS.T




Number of heads:	1
Description:	1 x 6 W LED 4000 K CRI>90 1 x 877 lm
Luminaire efficiency:	101.05 lm/W
Fixture consumption:	7.06 W
Operation Range:	350 mA
Number of circuits:	1
Driver positioning:	Remote
Control gear:	350 mA not included
Control gear type:	Electronic
Cable entry:	Brass cable gland M12 Ø 3.5/7 mm
Dimmer type:	Dim based on driver
Daisy chain wiring:	External to the luminaire with IP68 connector available as an accessory
Cable type:	FR5FOEM7-AD8 2x0.5mm2
Cord length:	0.5m
Emergency:	Not available
Ambient temperature operating range:	-20 °C ÷ +35 °C

OPTICAL:

Beam angle:	55°
Swivel:	+/- 90°
Light distribution:	Symmetrical wide beam (45° - 125°)
Beam directionability:	Adjustable
Diffuser material:	Tempered glass 4mm
Diffuser finish:	Transparent - extra clear
Optics:	Reflector in anti-UV technopolymer with super pure aluminum metallization




LIGHTING SOURCE:

Light source:	LED
Type of bulb or LED	COB
Light source:	6W
Nominal LED emission:	877 lm
Color temperature:	4000K
Binning:	Step MacAdam 3
LED voltage range:	18V
Current:	350 mA
Color rendering index:	CRI90
Life Time LED:	60.000h - L80 - B10[t]
Luminaire emission:	1 x 713lm
LED / Bulb	Included



H(m)	φ (m)	lux med. 4000 K	lux max. 4000 K
5	5.2	20	37
4	4.1	31	57
3	3.1	54	101
2	2.1	123	228
1	1.0	490	913





H(m)	φ(m)	lux med. 4000 K	lux max. 4000 K
5	5.2	20	37
4	4.1	31	57
3	3.1	54	101
2	2.1	123	228
1	1.0	490	913



FINISH OPTIONS:

Standard Finishes

●.05 Anthracite grey (matt)

●.19 Light grey (matt)

Upon Request Finishes

●.01 White (matt)

●.45 Corten (matt)

●.62 Antique grey (matt)

●.80 Sand (matt)

●.02 Black (matt)

●.26 Luxury bronze

●.65 Blue (matt)

●.83 Green (matt)

ACCESSORIES:



Stake 170mm
AC203



Hood Maxisegno - Point
Spot 3
AC648



IP 68 fast connector 4P
AC204

DIMMING TYPE:

101. Non-dimmable

102. 0-10V dimmable