

Please read all instructions before attempting installation

- 1. To prevent personal injury or product damage, only licensed electricians should install.
- 2. To avoid electric shock or component damage, disconnect power before attempting installation or servicing.
- 3. This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- 4. Disconnect product and allow cooling prior to servicing.
- 5. Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- 6. To prevent product malfunction and/or electrical shock, this product must be properly grounded.
- 7. This luminaire is designed to operate in ambient temperatures ranging from -30°C to 40°C and to be horizontally mounted with the LEDs facing down.

Pendant with 3/4" NPS Conduit Installation

1. Loosen the screw on the side of the light, removing the bracket from the canopy light by pulling it out.	
2. Connect the wires threaded from the conduit and canopy, Black wire for Line, White for Neutral, Yellow/Green for ground.	
	Black Line
	White Putral
	Green/Yellow Green Ground
3.Screw the conduit into the hole on top of canopy light. Installation is complete.	

Surface Mounted with J-Box Installation

1. Loosen the screw on the side of the light, removing the bracket from the canopy light by pulling it out.



LITELUME ©Lite Lume Corporation 2018

info@litelume.con 833.LED.LUME

LED Parking Garage Ocular Installation Instructions





Adjustable CCT & Wattage Installation Instructions



www.litelume.com Page 2/3 info@litelume.com 833.LED.LUME Rev Date: 12/16/2024

LED Parking Garage Ocular Installation Instructions

Wiring Diagram



LITELUME[°] ©Lite Lume Corporation 2018