

Styk - Suspended

SIP12122 2 in

JOB NAME:

TYPE:

NOTES:

DESCRIPTION

Styk was built to provide the most lumens with the smallest luminaire package, while optimizing life. Not limited to decorative lighting, effective functional lighting is provided through the optimal light control in this minimal package. It's three optical offerings enable tremendous flexibility including wall washing, wall grazing, and asymmetric lighting solutions. The family features wall, ceiling, and pendant models in a variety of stylish, clean mounting options. Available in 1' to 8' lengths, Styk can be mounted individually or configured in runs.

FEATURES & BENEFITS

- Sleek 1.5" diameter housing
- A forward throw optic, for even wall wash illumination, is standard
- Symmetrical optic options are available for more volumetric illumination
- Lamp body can be rotated up to 330° and locks into position for precise fixture alignment
- Up to 1,450 lumens per foot delivered (with Forward Throw distribution)
- Anodized finish provides durable corrosion protection
- All visible fasteners are flush mounted, providing a clean design
- Handcrafted in USA




SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine
- **CRI:** 80+ (contact factory for 90+)
- **LUMEN MAINTENANCE:** L70 = >50,000 Hrs.
- **EFFICACY:** 102 lm/W delivered (with Forward Throw distribution)
- **CCT:** 3000K, 3500K, or 4000K
- **VOLTAGE:** 120-277V standard
- **DRIVER:** Includes one remote Class 2 power supply and enclosure, except 8FT-L113W which has two. 36" lead length standard; black power cord standard unless otherwise specified. Max distance to the driver (including OAH) is: #18

AWG = 50', #16 AWG = 75', #14 AWG = 100'. For extended distances, contact factory.

- **DIMMING:** 0-10V controls standard to 1%
- **EMERGENCY:** Emergency battery remote optional
- **INTEGRATED SURGE PROTECTION:** LED components are protected against minor surge events
- **CONSTRUCTION:** Extruded aluminum construction provides durable protection for internal components and is recyclable
- **FINISH:** Housing available in anodized finishes only. End caps and mounting components painted to match.
- **MODIFICATIONS:** Consult factory for all modification requests, including RGB and static LED colors
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS



1FT	W	L	OAH	MC
	2.2 in 5.6 cm	17.5 in 44.4 cm	36 in 91.4 cm	16.2 in 41.1 cm

Mounting Weight: Approximate: 5 lb (3 kg)

2FT	W	L	OAH	MC
	2.2 in 5.6 cm	29.2 in 74.2 cm	36 in 91.4 cm	28 in 71.1 cm

Mounting Weight: Approximate: 5 lb (3 kg)

3FT	W	L	OAH	MC
	2.2 in 5.6 cm	41 in 104.1 cm	36 in 91.4 cm	39.7 in 100.8 cm

Mounting Weight: Approximate: 5 lb (3 kg)

4FT	W	L	OAH	MC
	2.2 in 5.6 cm	52.5 in 133.4 cm	36 in 91.4 cm	51.2 in 130 cm

Mounting Weight: Approximate: 5 lb (3 kg)

5FT	W	L	OAH	MC
	2.2 in 5.6 cm	64.5 in 163.8 cm	36 in 91.4 cm	63.2 in 160.5 cm

Mounting Weight: Approximate: 10 lb (5 kg)

6FT	W	L	OAH	MC
	2.2 in 5.6 cm	78.2 in 198.6 cm	36 in 91.4 cm	77 in 195.6 cm

Mounting Weight: Approximate: 10 lb (5 kg)


8FT	W	L	OAH	MC
	2.2 in 5.6 cm	102.2 in 259.6 cm	36 in 91.4 cm	101 in 256.5 cm

Mounting Weight: Approximate: 10 lb (5 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/SIP12122. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply. Alternative wattages available upon request. Delivered lumens shown below are for Forward Throw distribution.

1 FOOT NOMINAL FIXTURE

- ☐ 1FT-L4W | White 4W LED Light Engine | Delivered Lumens: 407
- ☐ 1FT-L7W | White 7W LED Light Engine | Delivered Lumens: 712
- ☐ 1FT-L14W | White 14W LED Light Engine | Delivered Lumens: 1,424

2 FOOT NOMINAL FIXTURE

- ☐ 2FT-L8W | White 8W LED Light Engine | Delivered Lumens: 814
- ☐ 2FT-L14W | White 14W LED Light Engine | Delivered Lumens: 1,424
- ☐ 2FT-L28W | White 28W LED Light Engine | Delivered Lumens: 2,848

3 FOOT NOMINAL FIXTURE

- ☐ 3FT-L12W | White 12W LED Light Engine | Delivered Lumens: 1,220
- ☐ 3FT-L21W | White 21W LED Light Engine | Delivered Lumens: 2,136
- ☐ 3FT-L42W | White 42W LED Light Engine | Delivered Lumens: 4,271

4 FOOT NOMINAL FIXTURE

- ☐ 4FT-L16W | White 16W LED Light Engine | Delivered Lumens: 1,627
- ☐ 4FT-L28W | White 28W LED Light Engine | Delivered Lumens: 2,848
- ☐ 4FT-L56W | White 56W LED Light Engine | Delivered Lumens: 5,695

5 FOOT NOMINAL FIXTURE

- ☐ 5FT-L20W | White 20W LED Light Engine | Delivered Lumens: 2,034
- ☐ 5FT-L35W | White 35W LED Light Engine | Delivered Lumens: 3,560
- ☐ 5FT-L71W | White 71W LED Light Engine | Delivered Lumens: 7,221

6 FOOT NOMINAL FIXTURE

- ☐ 6FT-L24W | White 24W LED Light Engine | Delivered Lumens: 2,441
- ☐ 6FT-L42W | White 42W LED Light Engine | Delivered Lumens: 4,271
- ☐ 6FT-L85W | White 85W LED Light Engine | Delivered Lumens: 8,645

8 FOOT NOMINAL FIXTURE

- ☐ 8FT-L32W | White 32W LED Light Engine | Delivered Lumens: 3,254
- ☐ 8FT-L56W | White 56W LED Light Engine | Delivered Lumens: 5,695
- ☐ 8FT-L113W | White 113W LED Light Engine | Delivered Lumens: 11,492

See last page for finish options

B - VOLTAGE *

☐ 120-277V | Universal Voltage

C - LAMP OPTIONS *

Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.

☐ 3000K ¹ | 3000K CCT

☐ 3500K ² | 3500K CCT

☐ 4000K | 4000K CCT

¹ Apply .95 multiplier for delivered lumens

² Apply .97 multiplier for delivered lumens

D - MOUNTING *

MCS mount includes a 72" flexible conduit for connection to remote power supply. CAS mounts to standard 4" octagonal junction box. Additional mounting structure and hardware required (by others). The 8FT-L113W option has a power feed exiting through both stems.

☐ DF_MCS | 2.3" Mini Canopy (default)

☐ CAS | 5" Canopy and Stem with 15° Swivel



E - LINEAR RUN

Select this option only for runs longer than 8'. Continuous runs are supplied with one power supply per fixture. 8FT-L113W is not available with the RUN option. INSTALLATION NOTES: During installation the contractor is responsible to use actual fixtures to ensure accurate mounting centers from one fixture to the next along the length of the linear run.

☐ RUN ³ | Continuous Run OAL | Specify Length of Run

Length:

³ For a take-off and pricing, contact factory

F - EMERGENCY

☐ EMR | Emergency Battery Remote


G - OPTICAL DISTRIBUTION *

See IES zip file for photometrics for each distribution.

- ☐ **DF_FT** | Forward Throw (default)
- ☐ **SMA** ⁴ | Symmetric 60 Degree Beam - 120 Degree spread
- ☐ **SMB** ⁵ | Symmetric 30 Degree Beam - 60 Degree spread

⁴ Delivered lumens are 90% of the output shown under Light Source; see IES file

⁵ Delivered lumens are 104% of the output shown under Light Source; see IES file



H - OPTIONS

- ☐ **F** | Fusing

I - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard

Length:

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Anodized

AN04 Anodized		AN08 Anodized Black	
-------------------------	---	-------------------------------	---

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.