




Profile Series | PRFL-24-DI-WM

Date	Notes
Project	
Type/Qty	

Features

Extruded aluminum housing w/flat or round end caps.
LED optimized optics for smooth, efficient illumination.
Individual fixtures, continuous rows or custom patterns.
Programmable driver for custom lumen packages.
0-10V dimming to 1% standard. Dim-to-off available.
DMX, Lutron and DALI protocols also available.
Sensor Ready for wireless Smart Lighting Solutions.
80/90CRI, Tunable White, RGBW & RGBWW.
Advanced Color (RGBW) w/pixel control to 5".
Bios SkyBlue™ circadian solutions available.
DLC V5.1 Standard Listed up to 122 LPW.
Declare Red List Approved.



Flush Lens
w/Clear Acrylic
Dust Cover

See page 5 for
additional optics
and mounting
options.

Round
End Caps

Ordering Guide

RS Declare. BAA



MODEL	OPTICS (D/I)	LED ¹	LUMENS ²	LENGTH	MOUNTING ⁴	FINISH	OPTIONS
PRFL-24-DI	/				WM		
PRFL-24-DI Direct/Indirect	STANDARD (D/I) FL/CA = Flush Opal Acrylic Direct (snap-in) / Clear Acrylic Indirect OPTIONAL (D) DL = 1" Drop Opal Acrylic (snap-in) SCB = Cross Baffle w/acrylic overlay AS* = Asymmetric (snap-in) CM* = Collimating BW* = Batwing (snap-in) OPTIONAL (I) FL = Flush Opal (snap-in) SI = Satin Ice AS* = Asymmetric CM* = Collimating BW* = Batwing *Semi-diffuse acrylic lenses.	STATIC WHITE 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K BIOS SkyBlue Spectrally optimized circadian solutions. TUNABLE WHITE (2700K-6500K) 2DIM10 = for 0-10V 2DMX = for DMX 2ESN = for Philips 2CAS = for Casambi 2LUT = for Lutron DIM-TO-WARM (2700K-6500K) DTW = Dim-to-Warm RGB + WHITE RGB = RGB RGBW = RGBW RGBWW = RGBWW ADVANCED COLOR 125mm incremental pixel color control for chase and animated effects.	LO = 1169/ft (10W/ft, 117LPW) SO = 1557/ft (13W/ft, 117LPW) HO = 1948/ft (17W/ft, 117LPW) DLC V5.1³ SO = 1590/ft (13W/ft, 122LPW) CUSTOM LUMENS For custom lumens please specify < HO.	2 = 2 ft 3 = 3 ft 4 = 4 ft 5 = 5 ft 6 = 6 ft 7 = 7 ft 8 = 8 ft For other enter row length (48 = 48 ft)	WM = Wall Mount	W = White CC = Custom Color AMW = Anti-Microbial White	DIMMING DRIVERS DIM10 = 0-10V (1%) - Standard DTO = 0-10V (Dim-to-Off) DIMST = 0-10V Step Dimming 347 = 0-10V (347V) DIMSR = DALI Sensor Ready (5.0%) DALI = DALI (5.0%) DMX = DMX LUTRON™ DIMMING DRIVERS LDE1 = Hi-Lume 1% EcoSystem LD2 = Digital 1% (DALI-2) L3DA3W = Hi-Lume 1% 3-Wire SENSORS & CONTROLS⁵ EMERGENCY BATTERY⁶ EMC = Emergency Circuit GTD = Generator Transfer Device EPC4 = 4W Integral Battery EPC6 = 6.5W Integral Battery EPC10 = 10W Integral Battery EPC12 = 12W Integral Battery WIRING & OTHER FWH = Flexible Wiring Harness GTD = Generator Transfer Device TCW = Two Circuit Wiring RE = Round End Caps

¹All LED, BIOS, Tunable White, DTW, and RGB/W options and Ordering Codes page 2.

²Lumens at 80CRI, 3500K, FL/CA lens. Photometry page 4.

³**DLC** options are limited to FL/CA optics, static white 35/40K CCT @ 80CRI, SO lumens, all mounting, all finishes, and all options excluding DIMST.

⁴See page 4 for mounting option details.

⁵All Sensor & Control options page 2.

⁶EPC6 is standard unless otherwise specified. EPC not for DMX drivers.

BAA letter of compliance available at www.dayolite.com.

RS 10 Day Rapid Ship options in **blue**. Details page 5.

LED, BIOS, Sensor & Control Ordering Codes**LED****Static White**

30 = 3000K 80 CRI
 35 = 3500K 80 CRI
 40 = 4000K 80 CRI
 50 = 5000K 80 CRI

927 = 2700K 90 CRI
 930 = 3000K 90 CRI
 935 = 3500K 90 CRI
 940 = 4000K 90 CRI

Tunable White¹
(2700K-6500K)

2DIM10 = 0-10V 80 CRI
 2DMX = DMX 80 CRI
 2CAS = Casambi Wireless 80 CRI
 2ESN = Philips EasySense 80 CRI
 2LUT = Lutron (LD2) 80 CRI

92DIM10 = 0-10V 90 CRI
 92DMX = DMX 90 CRI
 92CAS = Casambi Wireless 90 CRI
 92ESN = Philips EasySense 90 CRI
 92LUT = Lutron (LD2) 90 CRI

Dim-to-Warm²

DTW = 6500K-2700K 80 CRI
 9DTW = 6500K-2700K 90 CRI

RGB/W³

RGB = RGB only
 RGB27 = RGB w/2700K
 RGB30 = RGB w/3000K
 RGB35 = RGB W/3500K
 RGB40 = RGB w/4000K
 RGB50 = RGB w/5000K
 RGBWW = RGB w/2700K-6500K

Single Color⁴

RED = Red
 BLU = Blue
 GRN = Green
 AMB = Amber

Advanced Color⁵

Advanced Color options combine RGB or RGBW with multi-pixel control for advanced chases, animated visual effects and other programmable scenes with 125mm pixel granularity.

ACRGB = RGB only
 AC27 = RGB w/2700K
 AC30 = RGB w/3000K
 AC40 = RGB w/4000K

BIOS SkyBlue

BIOS SkyBlue biological technology brings the benefits of blue skies inside. BIOS SkyBlue is the only spectrally optimized circadian solution to target the region that drives wellness benefits including: increased alertness, enhanced productivity, better mood, and better sleep. More information may be found at www.bioslighting.com or by contacting Day-O-Lite directly. All options for 0-10V control.

BIOS Biological Static

For daytime applications. BIOS Static Biological LED features key BIOS SkyBlue (490nm) for maximum daytime circadian impact.

B30 = 3000K
 B35 = 3500K
 B40 = 4000K

BIOS Biological Dynamic White

Designed to transition from daytime to evening in a dim-to-warm protocol. The daytime CCT includes full BIOS SkyBlue (490nm) for maximum daytime circadian impact, while the evening spectrum removes BIOS SkyBlue for minimal circadian stimulus after hours.

B30D = 3000K-2700K
 B35D = 3500K-3000K
 B40D = 4000K-3500K

BIOS Biological Tunable White

Designed to transition from daytime to evening in a tunable white protocol. The daytime CCT includes full BIOS SkyBlue (490nm) for maximum daytime circadian impact, while the evening spectrum removes BIOS SkyBlue for minimal circadian stimulus after hours.

B30T = 3000K-2700K
 B35T = 3500K-2700K
 B40T = 4000K-2700K

¹Tunable white may be controlled by a number of dimming protocols as shown.

²Dim-to-Warm mimics incandescent dimming by warming the CCT from 6500K to 2700K as light levels are dimmed.

³All RGB, RGBW and RGBWW options for DMX control (by others). 80 CRI standard.

⁴Single colors are constant voltage LEDs. Dimming requires ELV controller (by others).

⁵White limited to 100L/ft.

Sensors & Controls**Sensors***

AVO = Avi-On Occ/Day
 AVM = Avi-On Occ (Microwave)
 BNV = BubblyNet Occ/Day
 ENC = Encelium Occ/Day
 ENL = EnLighted Occ/Day/Temp
 LEG = Legrand Occ/Day
 ANW = Lutron Athena Occ/Day
 VIVE = Lutron Vive Occ/Day
 NLT = Acuity nLight Occ/Day
 NXC = Current NX Occ/Day
 ESN = Philips EasySense Occ/Day
 WWL = Cooper WaveLinx Occ/Day

Wireless Control*

CAS = Casambi


*Sensors and control options to be commissioned wirelessly in the field by qualified controls personnel with applicable apps (by others).

Individual Fixtures & Continuous Rows

NOMINAL LENGTH	ACTUAL LENGTH	WALL BRKTS.
4'	44 1/2"	2
8'	89"	3
12'	133 1/2"	5
16'	178"	8
20'	222 1/2"	8
24'	267"	9

Individual fixtures and rows are continuously illuminated and joined with included aligner brackets and hardware. Power feed locations and mounting locations are shown below.

Continuous rows longer than 8' and patterns, including EPC/EMC and sensor locations must be approved prior to manufacturing.




Emergency & Sensor Locations

EPC will control entire length of individual fixtures. Individual fixtures of differing lengths will deliver the same lumens under EPC power (a 4' fixture will deliver the same total lumens over half the length of an 8' fixture). EMC controlled individual fixtures will deliver lumens per foot as originally specified, unless dimmed at time of power loss. Consult factory for EMC dimming overRide device.


4' Individual 

8' Individual 

For individual fixtures to 8' EPC/EMC will power entire fixture.

24' Row (3x8') 

For continuous rows longer than 8' one EPC/EMC will be located in the feed section (end-left) of the row as shown below.

24' Row (3x8') 


If two EPC/EMC's are required their default locations will be in the feed section (end-left) and last section (end-right) as below.

24' Row (3x8') 

Custom placement of one or more EPC/EMC's must be clearly identified during ordering.


8' Individual 

SENSORS (Integral) for individual fixtures will control entire length of fixture and will be located on feed end of fixture.


24' Row (3x8') 

SENSORS for rows by default will control the feed section (end-left) of the row. Sensors can control more than an 8' section within a row. Consult factory for sensor/section options, or for multiple sensors in a continuous row.


Mounting & Optics Details



FL Lens Direct
CA Lens Indirect




SCB Lens Direct
CA Lens Indirect



DL Lens Direct (1" Drop)
CA Lens Indirect

Photometry



Flush Lens

PRFL-24-DI-FL/CA-35-**LO-4**
Flush Lens Direct w/Clear
Acrylic Dust Covers

3500K CCT
WATTS: 40
LUMENS: 4677
LPW: 117

PRFL-24-DI-FL/CA-35-**SO-4**
Flush Lens Direct w/Clear
Acrylic Dust Covers

3500K CCT
WATTS: 53
LUMENS: 6228
LPW: 117

PRFL-24-DI-FL/CA-35-**HO-4**
Flush Lens Direct w/Clear
Acrylic Dust Covers


3500K CCT
WATTS: 67
LUMENS: 7790
LPW: 117

PRFL-24-DI-FL/CA-35-**S3D-4**
DLC V5.1 Standard

3500K CCT
WATTS: 52
LUMENS: 6360
LPW: 122

PRFL-24-DI-F/CA-40-**S4D-4**
DLC V5.1 Standard

4000K CCT
WATTS: 52
LUMENS: 6370
LPW: 122



Batwing Lens

PRFL-24-DI-FL/BW-35-**LO-4**
Flush Lens Direct
Batwing Lens Indirect


3500K CCT
WATTS: 40
LUMENS: 44192
LPW: 114

PRFL-24-DI-FL/BW-35-**SO-4**
Flush Lens Direct
Batwing Lens Indirect

3500K CCT
WATTS: 53
LUMENS: 5590
LPW: 114

PRFL-24-DI-FL/BW-35-**HO-4**
Flush Lens Direct
Batwing Lens Indirect

3500K CCT
WATTS: 67
LUMENS: 6988
LPW: 110



Asymmetrical Lens

PRFL-24-DI-FL/AS-35-**LO-4**
Flush Lens Direct
Asymmetrical Indirect


3500K CCT
WATTS: 40
LUMENS: 4335
LPW: 117

PRFL-24-DI-FL/AS-35-**SO-4**
Flush Lens Direct
Asymmetrical Indirect

3500K CCT
WATTS: 53
LUMENS: 5780
LPW: 117

PRFL-24-DI-FL/AS-35-**HO-4**
Flush Lens Direct
Asymmetrical Indirect

3500K CCT
WATTS: 67
LUMENS: 7225
LPW: 114



Collimating Lens

PRFL-24-DI-FL/CM-35-**LO-4**
Flush Lens Direct
Collimating Lens Indirect

3500K CCT
WATTS: 40
LUMENS: 4404
LPW: 120

PRFL-24-DI-FL/CM-35-**SO-4**
Flush Lens Direct
Collimating Lens Indirect

3500K CCT
WATTS: 53
LUMENS: 5872
LPW: 119

PRFL-24-DI-FL/CM-35-**HO-4**
Flush Lens Direct
Collimating Lens Indirect

3500K CCT
WATTS: 67
LUMENS: 7340
LPW: 116

3500K @ 80CRI, 4', 43% Direct, 57% Indirect Distribution, FL/CA lens.

Use the following multipliers for other CCTs: 2700K x 0.96, 3000K x 0.98, 4000K x 1.02, 5000K x 1.03. IES files @ www.dayolite.com

Specifications

CONSTRUCTION: Extruded aluminum housing. 20 gauge cold rolled steel internal components.

REFLECTOR: Die-formed steel finished in highly reflective baked white enamel with pre-finished reflective LED tray.

OPTICS: Direct opal acrylic Flush lens is standard. 1" acrylic Drop lens, Steel Cross Baffle with acrylic overlay optional. Indirect Clear acrylic dust covers standard, Flush lens, Satin Ice, Asymmetrical, Batwing, Collimating and Black Out lenses available.

LED: Static white LED modules in 27/30/35/40 & 50K CCT, 80/90CRI. Lumen maintenance minimum $L_{70} = 50,000$ hours. 3 SDCM color consistency. BIOS SkyBlue, RGB, RGBW and Tunable White and Advanced Color options available.

DRIVER: Standard driver is Class 2 AOC 0-10V to 1%, 120/277V input, PF > 90%, THD < 20 @ 120V. Additional dimming protocols available. All drivers prewired from factory for connection to control system (by others). Field replaceable.

MOUNTING: Standard installation is wall mount with included mounting brackets and hardware. Requires single-gang j-box supplied by others.

FINISH: Housing and components finished in baked white enamel.

CERTIFICATION: cETLus listed conforming to UL STD. 1598 and certified to CSA STD C22.2 NO. 250.0. Suitable for dry & damp locations. Union Made in the United States of America. I.B.E.W., ADA and BAA compliant, DLC V5.1 Standard Listed. Declare Red List Approved.

LEGAL: Day-O-Lite, a division of SCW Corporation. All rights reserved. The Day-O-Lite logo is a registered trademark of SCW Corporation. Day-O-Lite reserves the right to change specifications without notice for product improvement.

Rapid Ship Program

Rapid Ship products are estimated to ship 10 business days or less from the morning the order is received and confirmed. Linear rows will ship 10 business days or less from the day the layout drawings are approved. Orders confirmed and layouts approved after 12:00 p.m. Eastern Time are estimated to ship 10 days or less from the following business morning. Please refer to complete program Terms & Conditions at www.dayolite.com.

Rapid Ship options are limited to those highlighted in **blue** on the Ordering Guide. 400' max individual or continuous row allowed. Consult factory for additional information.