


<b>Series</b>	ACOUSTIC FLOWER RING LIGHT SERIES	<b>Model</b>	FLOWER 3S/ FLOWER 5UDS/ FLOWER 25S/ FLOWER 26S
---------------	-----------------------------------	--------------	--




<b>Project:</b>	
<b>Type:</b>	
<b>Notes:</b>	
<b>Overview</b>	
Acoustic flower ring series Light are versatile architectural lighting solution, combin with acoustic panel shape, with direct illumination, direct and indirect, inner illuminating. From 2ft dia to 5ft dia, with Central canopy suspended, direct suspension for optional.	



<b>Certificate</b>	<b>Features</b>
	<ol style="list-style-type: none"> <li>The diameter size to choose from ranging from 2ft to 5ft.</li> <li>2 color finishes(black, white), can be customized.</li> <li>Operation Voltage: AC120-277V, 0-10V dimming and non-dimmable for optional</li> <li>Aluminum body construction</li> <li>36 acoustic felt colors</li> <li>Efficiency: <math>\geq 70\text{lm/w}</math></li> </ol>

<b>Type</b>	Suspended - Down
-------------	------------------




























<b>Size</b>
-------------



Model No.	Dimension		Driver quantity	Section quantity	Dimension code	Direct Lumen/Watt	Indirect Lumen/Watt
	D	H					
FLOWER 3-S-40W-ACFL	23.6"(600mm)	5.2"(132mm)	1	1	D24	2800/40W	/
FLOWER 3-S-50W-ACFL	35.4"(900mm)	7.6"(192mm)	1	1	D35	3500/50W	/
FLOWER 3-S-80W-ACFL	47.2"(1200mm)	9.8"(247mm)	2	1	D47	5600/80W	/
FLOWER 3-S-100W-ACFL	59.1"(1500mm)	11.9"(303mm)	2	1	D59	7000/100W	/
FLOWER 5-UDS-65W-ACFL	23.6"(600mm)	6.4"(162mm)	2	1	D24	2800/40W	1750/25W
FLOWER 5-UDS-80W-ACFL	35.4"(900mm)	8.8"(222mm)	2	1	D35	3500/50W	2100/30W
FLOWER 5-UDS-120W-ACFL	47.2"(1200mm)	11.0"(277mm)	3	1	D47	5600/80W	2800/40W
FLOWER 5-UDS-135W-ACFL	59.1"(1500mm)	13.1"(333mm)	3	1	D59	6300/90W	3150/45W
FLOWER 25-S-32W-ACFL	23.6"(600mm)	4.9"(126mm)	1	1	D24	2200/32W	/
FLOWER 25-S-40W-ACFL	35.4"(900mm)	7.3"(186mm)	1	1	D35	2800/40W	/
FLOWER 25-S-70W-ACFL	47.2"(1200mm)	9.5"(241mm)	2	1	D47	4900/70W	/
FLOWER 25-S-80W-ACFL	59.1"(1500mm)	11.7"(297mm)	2	1	D59	5600/80W	/
FLOWER 26-S-32W-ACFL	23.6"(600mm)	4.9"(126mm)	1	1	D24	2200/32W	/
FLOWER 26-S-40W-ACFL	35.4"(900mm)	7.3"(186mm)	1	1	D35	2800/40W	/
FLOWER 26-S-70W-ACFL	47.2"(1200mm)	9.5"(241mm)	2	1	D47	4900/70W	/
FLOWER 26-S-80W-ACFL	59.1"(1500mm)	11.7"(297mm)	2	1	D59	5600/80W	/



## PRODUCT SPECIFICATION


Model No.	Installation		Power		Acoustic	CRI	CCT		Control		Body Color		Acoustic Color	Dimension code
	S	Suspended	40W	For size D23.6"	ACFL	80+	30K	3000K	STD	Non-dimming	SW	Matt white	Acoustic Color Code	D24
FLOWER 3			50W	For size D35.4"		90+	35K	3500K	DIM	0-10V dimming	SB	Matt black		D35
			80W	For size D47.2"			40K	4000K			RAL	Customized color		D47
			100W	For size D59.1"										D59
FLOWER 5	UDS	Suspended	65W	For size D23.6"	ACFL									D24
			80W	For size D35.4"										D35
			120W	For size D47.2"										D47
			135W	For size D59.1"										D59
FLOWER 25	S	Suspended	32W	For size D23.6"	ACFL									D24
			40W	For size D35.4"										D35
			70W	For size D47.2"										D47
			80W	For size D59.1"										D59
FLOWER 26	S	Suspended	32W	For size D23.6"	ACFL									D24
			40W	For size D35.4"										D35
			70W	For size D47.2"										D47
			80W	For size D59.1"										D59

Acoustic Color Code	Color Swatches							
								
								
								
								
								

**Order Example:** FLOWER 3-S-40W-ACFL-90-30K-DIM--SW-NSAC-001 141-D24

# PRODUCT SPECIFICATION

Light distribution	Optical system																																																			
	<table border="1" style="margin: auto; border-collapse: collapse;"> <thead> <tr> <th>Height</th> <th>Center h</th> <th>Diameter</th> </tr> </thead> <tbody> <tr><td>1 m</td><td>3254.54 in</td><td>338.36cm</td></tr> <tr><td>2 m</td><td>813.64 in</td><td>678.36cm</td></tr> <tr><td>3 m</td><td>361.62 in</td><td>1014.54cm</td></tr> <tr><td>4 m</td><td>203.41 in</td><td>1352.73cm</td></tr> <tr><td>5 m</td><td>130.18 in</td><td>1690.91cm</td></tr> <tr><td>6 m</td><td>90.40 in</td><td>2029.09cm</td></tr> <tr><td>7 m</td><td>66.42 in</td><td>2367.27cm</td></tr> <tr><td>8 m</td><td>50.85 in</td><td>2705.45cm</td></tr> <tr><td>9 m</td><td>40.18 in</td><td>3043.63cm</td></tr> <tr><td>10 m</td><td>32.55 in</td><td>3381.82cm</td></tr> <tr><td>11 m</td><td>26.90 in</td><td>3720.00cm</td></tr> <tr><td>12 m</td><td>22.60 in</td><td>4058.18cm</td></tr> <tr><td>13 m</td><td>19.25 in</td><td>4396.36cm</td></tr> <tr><td>14 m</td><td>16.60 in</td><td>4734.54cm</td></tr> <tr><td>15 m</td><td>14.46 in</td><td>5072.72cm</td></tr> <tr><td>16 m</td><td>12.71 in</td><td>5410.91cm</td></tr> </tbody> </table>  <p style="text-align: center;">Beam Angle: 118.80°(50%Imax)</p>	Height	Center h	Diameter	1 m	3254.54 in	338.36cm	2 m	813.64 in	678.36cm	3 m	361.62 in	1014.54cm	4 m	203.41 in	1352.73cm	5 m	130.18 in	1690.91cm	6 m	90.40 in	2029.09cm	7 m	66.42 in	2367.27cm	8 m	50.85 in	2705.45cm	9 m	40.18 in	3043.63cm	10 m	32.55 in	3381.82cm	11 m	26.90 in	3720.00cm	12 m	22.60 in	4058.18cm	13 m	19.25 in	4396.36cm	14 m	16.60 in	4734.54cm	15 m	14.46 in	5072.72cm	16 m	12.71 in	5410.91cm
Height	Center h	Diameter																																																		
1 m	3254.54 in	338.36cm																																																		
2 m	813.64 in	678.36cm																																																		
3 m	361.62 in	1014.54cm																																																		
4 m	203.41 in	1352.73cm																																																		
5 m	130.18 in	1690.91cm																																																		
6 m	90.40 in	2029.09cm																																																		
7 m	66.42 in	2367.27cm																																																		
8 m	50.85 in	2705.45cm																																																		
9 m	40.18 in	3043.63cm																																																		
10 m	32.55 in	3381.82cm																																																		
11 m	26.90 in	3720.00cm																																																		
12 m	22.60 in	4058.18cm																																																		
13 m	19.25 in	4396.36cm																																																		
14 m	16.60 in	4734.54cm																																																		
15 m	14.46 in	5072.72cm																																																		
16 m	12.71 in	5410.91cm																																																		

Accessories
<div style="border: 1px solid black; padding: 5px; display: inline-block; margin-bottom: 10px;"> <p>A.Mounting Bracket                      B.Anchor Screws                      C.Plastic Anchors                      D.Bracket Screws                      E.Canopy Screws                      F.Wire Connectors</p> </div> 

Material	LED system
<b>LED Driver</b> ARCATA or Equivalent, AC120-277V, PF>0.9, no flicker, UL Cert, Class P	<b>LED</b> Samsung 2835, 3V, 150mA
<b>Alu PCB</b> 2.0W/M/K, UL Cert	<b>CCT</b> 2700K, 3000K, 3500K, 4000K and 5000K with a great color consistency (within 6-step MacAdam ellipse)
<b>Housing</b> Alumium6063, painting.	<b>Led life</b> Minimum 50,000h with 70% of lumen maintenance in 25C ambient temperature, in compliance with IES LM-80 testing measurements.
<b>Lens</b> PC, UL-94VO, Anti-UV	<b>Operation temp</b> minus 20C to 40C (centigrade)
CIP Lighting reserves the right to make any design changes for continuous improvement without notification, contact us for the latest technical information!	<b>File name</b> NS/SS-LL0113-ACFL REV1.0