

# ICONA 3

## 3" Cylinder Round Surface

PART NUMBER:

TYPE:

JOB NAME:

### ORDERING INFORMATION

#### 1 PRODUCT FAMILY

- ICY3R** 3" Cylinder Round

#### 2 FINISH

- BLS** BLACK SATIN  
 **WHS** WHITE SATIN  
 **SLV** SILVER

#### 3 WATTAGE

- 5** 5 Watts  
 **8** 8 Watts  
 **10** 10 Watts  
 **13** 13 Watts  
 **16** 16 Watts  
 **19** 19 Watts

#### 4 VOLTAGE

- UNV1** 120-277V (0-10V Dimming or TRIAC Dimming)

#### 5 CRI

- 90** 90 CRI (Standard)

#### 6 COLOR TEMPERATURE

- 2700** 2700k  
 **3000** 3000K  
 **3500** 3500k  
 **4000** 4000K

#### 7 BEAM OPTIONS

- N** Narrow Beam, 15 deg  
 **M** Medium Beam, 24 deg  
 **W** Wide Beam, 36 deg  
 **F** Flood Beam, 60 deg

#### 8 TRIM OPTIONS

- WT** White Trim  
 **BT** Black Trim  
 **GT** Gold Trim  
 **CT** Chrome Trim  
 **WW** White Wall Wash  
 **BW** Black Wall Wash  
 **DL** 1" Drop Lens

#### 9 Mounting

- SM** Surface Mount

#### 10 Ceiling Mounting

- RJ** Recessed Flat Canopy  
 **SJ** Surface Mounted Jbox



### SPECIFICATIONS

- SIZES:** 2.96" Wide. 10" Tall,
- CONSTRUCTION:** Constructed of extruded aluminum.
- OPTICS:** Available in 15, 24, 36 or 60 degree options. Optics are interchangeable and can be easily swapped in the field
- MOUNTING CONFIGURATIONS:**  
For Recessed J-box  
If recessed J-box is existing (3" octagon, 4" octagon and 4" round), the cylinder can be mounted directly to recessed mounted junction box.  
  
For Surface Mount J-box  
If standard 4" octagonal J-box is surface mounted, a Ø5.97" round x 2.38" deep canopy with conduit cutout is provided for mounting. Conduit cutout canopy has 4 key slots, one in each side, and can be configured to accommodate any ceiling layout using ½" or ¾" conduit. Conduit cutout canopy is provided white and black powder coat painted finish.
- DRIVERS:** Class 2 LED drivers are 120-277V and 0-10V dimming to 1% or Triac dimming (120V)

**Trim Options:**




- LED:** COB LED's are mounted to metal surface to maximize heat dissipation. Available in 2700, 3000, 3500 or 4000K. Standard 90CRI

**ILLUMINATION: PERFORMANCE**


Wattage Selectable	15°/3000K/White		24°/3000K/White		36°/3000K/White		60°/3000K/White	
	Efúcacy	Lumens	Efúcacy	Lumens	Efúcacy	Lumens	Efúcacy	Lumens
5W	115LM/W	575LM	115LM/W	575LM	105LM/W	525LM	95LM/W	475LM
8W	115LM/W	920LM	120LM/W	960LM	105LM/W	840LM	95LM/W	760LM
10W	115LM/W	1150LM	115LM/W	1150LM	105LM/W	1050LM	95LM/W	950LM
13W	110LM/W	1430LM	115LM/W	1490LM	105LM/W	1365LM	90LM/W	1170LM
16W	105LM/W	1680LM	110LM/W	1760LM	100LM/W	1600LM	80LM/W	1280LM
19W	100LM/W	1900LM	105LM/W	1995LM	95LM/W	1805LM	80LM/W	1520LM

- FINISHES:** Powder coated finish applied to housing and canopies. Standard Black, White or Silver. Consult factory for other finish options
- LISTINGS:** UL listed for damp indoor locations.
- WARRANTY:** 5 year limited warranty on LED and electronic parts. Consult terms and conditions for full details.

### RENDERINGS AND DIMENSIONS




Surface Conduit cutout mounting example



**SURFACE OPTIONS**

Surface Mount To Recessed Junction Box



Surface Mount With Conduit Cutout For Surface Mounted 4" Octagonal Junction Box

